



Alfa Laval ALS

Side-mounted agitator for tank mixing and blending in hygienic applications

Introduction

The Alfa Laval ALS is a side-mounted agitator for hygienic mixing and blending in atmospheric and pressurized tanks. Its versatile, modular and hygienic design enables customization to meet the requirements of virtually any duty and ensures cost-effective, energy-efficient operation. Exceptional cleanability through Cleaning-in-Place makes the ALS agitator ideal for use in sterile and aseptic applications. An ATEX-certified version is available for use in potentially explosive environments.

Applications

The ALS side-mounted agitator is designed for a wide range of tank mixing and blending duties across the dairy, food, beverage, brewery, personal care, biotechnology and pharmaceutical industries.

Duties

Keeping media homogeneous

Mixing and solutions

Dispersing

Suspension

Heat transmission

Typical examples

Milk storage tanks, cream tanks, mixed products tanks, UHT, and products storage tanks

Fluid and fluid mixing, drinking yoghurt and fruit mix tanks, flavoured milk mix tanks, and syrup mix tanks

Powder protein and oil mix tanks, micro salt and milk product mix tanks

Fluids with particles, juice tanks, crystallizing tanks, etc

Circulation of media in tank with dimple jacket (cooling or heating)

Benefits

- Versatile, modular, hygienic design
- Can be configured for minimum energy consumption
- Gentle product treatment
- More uptime and higher yields due to low maintenance requirements
- Meets EU and US standards and regulations such as EHEDG, USDA, FDA, 3-A Sanitary Standards

Standard design

The Alfa Laval ALS side-mounted agitator consists of a drive unit with bearing frame, shaft with special shaft seal, and specially designed energy-saving impeller (EnSaFoil) with two or three blades. The complete Alfa Laval agitator range includes top-, bottom- and side-mounting models.



Working principle

The Alfa Laval ALS side-mounted agitator has an electrical drive motor that transmits the energy required for mixing and blending, either directly or via a gearbox, to the agitator shaft. The shaft rotates, turning the EnSaFoil impeller. The impeller movement creates a high flow with low shear due to the highly effective axial pumping effect on the liquid in the tank. This results in effective mixing and blending of the entire contents of the tank.

Options

- Welding flange
- Stainless steel cover for motor/gear motor
- Spare part kit
- ATEX version

Certification

Alfa Laval Q-doc and ATEX certifications available, depending on the individual configuration.



TECHNICAL DATA

Motor

Motor size and speed as required for duty.

As standard with IEC motor IP55, other types on request. As standard painted RAL5010.

Voltage and frequency

As standard for 3x380 to 420V, 50Hz - 3x440V to 480V, 60Hz. All motor voltages and frequencies are available.

Gears

Different gear types available according to configuration.

As standard filled with normal synthetic or mineral oil, optional: Food approved oil. As standard painted RAL5010.

Product wetted surface finish

Industrial, Shot peened

Ra < 3,2 µm

Hygienic, polished

Ra < 0,8 µm

Hygienic (UltraPure), polished or electro polished

Ra < 0,51 µm

PHYSICAL DATA

Materials

Steel parts:

EPDMAISI 316L (standard). Other materials on request.

Seal rubber parts (O-rings or bellows):

FPM/FEP (only for stationary o-rings)

FPM

Other materials on request.

Mechanical seal parts:

Carbon

Carbon (FDA)

Silicon carbide

Configurable design

Type ALS agitator design is fully configurable divided in the following elements:


- Drives (drive + shaft support + shaft diameter)
- Seal arrangements (oil trap + shaft seal type)
- Shaft (length)
- Energy Saving Foils (propeller type + surface finish)
- Options

Each element has a broad range of different characteristics which makes it possible to size the agitator for all applications and requirements.

Advantageous and profitable design

Each configuration offers a number of advantages, which are shown in the examples below:


Operation features	Due to
Low energy consumption	the wide range of high efficiency propellers and drive units makes it possible to design for low operational costs
Gentle product treatment	the wide range of high efficiency propellers makes it possible to design for low shear operation
Hygienic features	Due to
Easy external cleaning	stainless steel bearing frame design with O-ring seal (for wash down)
Connections inside the tank (risk zones) can be avoided	bearing frame drives with drive shaft and special internal shaft connection without having a flange coupling inside the tank
Good drip off properties	no plane surfaces or grooves on internal parts
Easy cleaning	no interior shadow sides between the blades and smooth surfaces
Maintenance features	Due to
All service (replacement of wear parts such as shaft seals, bearings etc.) can be done from outside of the tank	bearing frame drives with detachable shaft which can be dismantled from outside of the tank
Easy dismantling	use of spider type coupling and stainless steel parts (no corrosion)



Type ALS Configuration Side mounted agitators


Drives

Bearing frame size = xx
 Shaft diameter = yy
 (not used if xx = yy)




-ME-GR-Bxx(yy)

Description
 Stainless steel bearing frame and right angle gearbox




-ME-GC-Bxx(yy)

Description
 Stainless steel bearing frame and coaxial gearbox




-ME-Bxx(yy)

Description
 Stainless steel bearing frame and direct motor drive



-ME-GR-yy

Description
 Right angle gearbox, shaft mounted in hollow shaft of gearbox



-ME-GP-yy


Description
 Parallel shaft gearbox, shaft mounted in hollow shaft of gearbox

Seal arrangements




F-S1-

Description
 Seal flange with O-ring seal against tank flange, drain, oil trap (only geared versions) and shaft seal: single mechanical bellow seal




F-S2-

Description
 Seal flange with O-ring seal against tank flange, drain, oil trap (only geared versions) and shaft seal: mechanical non-bellow seal




LF-S1-

Description
 Lantern (spacer), seal flange with O-ring seal against tank flange, drain, oil trap (only geared versions) and shaft seal: single mechanical bellow seal




LF-S2-

Description
 Lantern (spacer), seal flange with O-ring seal against tank flange, drain, oil trap (only geared versions) and shaft seal: single mechanical non-bellow seal



LF-D-

Description
 Lantern (spacer), seal flange with O-ring seal against tank flange, drain, oil trap and shaft seal: double mechanical seal for high pressure applications and aseptic use



-ME-yyLF-S1-

Description
 Direct motor drive, shaft connected directly to motor, lantern (spacer), seal flange with O-ring seal against tank flange, drain and shaft seal: single mechanical bellow seal

Shaft



-S1111-

Length = IIII
 Description
 SS shaft, length according to application

Energy Saving Foils

Diameter = vv (125 mm to 1900 mm)




-PvvD3P

Description
 3 - bladed propeller, finish: polished Standard: Ra < 0.8 µm



-PvvD3PE

Description
 3 - bladed propeller, finish: polished and electro polished Standard: Ra < 0.8 µm



-PvvD3G

Description
 3 - bladed propeller, finish: shot peened

Dimensions

Propeller standard diameter range: ø125 mm to 1900 mm. Specific dimensions on the drive unit and propeller(s) will depend on the actual configuration selected.

Ordering

The following information is required to ensure correct sizing and configuration for ordering:

- Tank geometry
- Product properties
- Task of agitator
- Enquiry forms are available

Alfa Laval reserves the right to change specifications without prior notification.

How to contact Alfa Laval

Contact details for all countries are continually updated on our website. Please visit www.alfalaval.com to access the information direct.