

# Alfa Laval Unique RV-ST Regulating Valve

Control your flow

## Concept

Unique RV-ST is the third generation of Alfa Laval single seat regulating valves designed to meet the highest process demands of hygiene and safety. Built on a well-proven, platform from an installed base of more than one million valves, it is ideal for high volume, hygienic liquid processing applications where precision control of flow rate or pressure is required.

## Working principle

The valve is remote-controlled by a digital electro-pneumatic process controller. It has few and simple moveable parts which results in a very reliable valve.

## Technical data

Max. product pressure: . . . . . 10 bar (1000 kPa).  
 Min. product pressure: . . . . . Full vacuum.  
 Temperature range: . . . . . 10°C to +140°C (EPDM).  
 Air pressure: . . . . . 5 - 7 bar (500 to 700 kPa).

## Positioner data

Supply voltage: . . . . . 24 VDC +/- 10%  
 Working temperature: . . . . . 0 to 55 °C  
 Push-in fittings: . . . . . ø6mm or 1/4"  
 Protection class: . . . . . IP65 and IP67  
 Position detection module: . . . Contact-free, wear-free  
 Communication: . . . . . Analog

### 8692 Positioner – Top control with display

Setpoint setting: . . . . . 0/4 to 20mA and 0 to 5/10V  
 Output resistance: . . . . . 0/4 to 20 mA: 180Ω  
 0 to 5/10V: 19Ω  
 Power consumption: . . . . . < 5W  
 Cable gland: . . . . . 2xM16x1,5 (cable-ø10mm)  
 Max. wire diameter . . . . . 1.5 mm<sup>2</sup>

### 8694 Positioner – Basic control without display


Setpoint setting: . . . . . 0/4 to 20mA  
 Output resistance: . . . . . 180Ω  
 Power consumption: . . . . . < 3,5W  
 Cable gland: . . . . . 2xM16x1,5 (cable-ø10mm)  
 Max. wire diameter . . . . . 1.5 mm<sup>2</sup>




## Physical data

Material: . . . . . PPS, stainless steel  
 Cover: . . . . . PC  
 Seals: . . . . . EPDM  
 Product wetted steel parts: . . . . 1.4404 (316L)  
 External finish . . . . . Semi-bright (blasted)  
 Internal finish . . . . . Bright (polished), internal Ra < 0.8 µm  
 Other steel parts: . . . . . 1.4301 (304)  
 Plug seal: . . . . . EPDM  
 Other product wetted seals: . . . EPDM (standard)  
 Other seals: . . . . . NBR

## Valve Body Combinations



 Authorized to carry the 3A symbol

### Standard design

Designed to deliver years of reliable performance, it features a broad selection of stainless steel, tapered valve stems along with the Unique actuator to ensure an outstanding degree of precise product control. Rugged and long-lasting plastic stem bushings eliminate metal-to-metal galling. The stems are threaded to the actuator shaft, eliminating the coupling between the stem and the actuator, thereby ensuring proper alignment. The plug seal is a standard seal used for the entire Unique Series. Bushings at the end of the actuator cylinder support the stem and ensure perfect alignment.

### Other valves in the same basic design

- Unique Single Seat
- Standard valve
- Reverse acting valve
- Long stroke valve
- Manually operated valve
- Aseptic valve

### Options

- a. Male parts or clamp liners in accordance with required standard
- b. Product wetted seals in HNBR or FPM
- c. Maintainable actuator
- d. External surface finish blasted
- e. Optional plug seal: HNBR or FPM

### Note!


For further details, see instruction ESE02127

### Pressure drop/capacity diagrams

For  $\Delta P = 100 \text{ kPa (1bar)}$ .


#### Valve Size 1.5"

Kvq [m<sup>3</sup>/h]




#### Valve Size 2"

Kvq [m<sup>3</sup>/h]




**Valve Size 2.5"**

Kvq [m³/h]




**Valve Size 3"**

Kvq [m³/h]



**Valve Size 4"**

Kvq [m³/h]



\* Recommended working area

**Note!**

For the diagrams the following applies

Medium: Water (20° C)



----- (dotted line) = Kv 49

Alfa Laval recommend max. flow velocity in tubing and valves to be 5 m/sec.

Pressure data

Table 1 - Shut-off valves

Max. pressure in bar without leakage at the valve seat

Actuator / Valve body combination and direction of pressure	Air pressure [bar]	Plug position	Valve size [mm]				
			DN40/38	DN50/51	DN65/63.5	DN80/76.1	DN100/101.6
	6	NO	7.60	9.60	5.60	7.20	4.80
		NC	6.29	7.20	4.20	6.40	4.20

- A = Air
- P = Product pressure
- AC = Air closes
- SC = Spring closes

Valve Sizing

Flow Coefficients (Kv)

The following formula and flow coefficient values enable you to select the correct regulating valve for your application.

Formula for water and other products with a specific gravity equal to 1.0:

$$Kv = \frac{Q}{\sqrt{\Delta P}}$$

Formula for products with a specific gravity other than to 1.0:

$$Kv = \frac{Q}{\sqrt{\Delta P / SG}}$$

Where:

- Q = Product flow rate in m<sup>3</sup> per hour
- SG = Specific gravity of product
- Δ P = Pressure drop across valve in bar (inlet pressure minus outlet pressure)

Example of Kv Calculation:


Determine the proper size valve for 60 m<sup>3</sup> per hour of water.

- Inlet pressure of 3 bar
- Outlet pressure of 1,5 bar

**Solution:** Inlet pressure (A) minus outlet pressure (B):

$$\Delta P = 3 \text{ bar} - 1,5 \text{ bar} = 1,5 \text{ bar}$$


$$Kv = \frac{60}{\sqrt{1,5}} = 49$$



How to Use Data to Select Valve Size

After the Kv factor for a specific application has been calculated, locate the factor on the following page. Choose the curve closest to the 50% stroke.

Using the above example, refer to the chart on the previous page you will find that the Kv factor (49) is marked on the chart. You will find that a 2" valve crosses 1 Kv curve, 2½" 1 curve, 3" 3 curves and 4" 3 curves. The correct valve size to use is 2" because Kv 49 crosses the curve closest to the optimum operating point 50%. Alternatively the 4" valve is also close to the 50%.



**Dimensions (mm)**


Size	38 mm	51 mm	63.5 mm	76.1 mm	101.6 mm	DN 40	DN 50	DN 65	DN 80	DN 100
A (with positioner 8694)	450	499	525	558	603	451	500	525	562	606
A (with positioner 8692)	487	536	562	595	640	488	537	562	599	643
OD	38	51	63.5	76.1	101.6	41	53	70	85	104
ID	34.8	47.8	60.3	72.9	97.6	38	50	66	81	100
t	1.6	1.6	1.6	1.6	2	1.5	1.5	2	2	2
E	49.5	61	81	86	119	49,5	61	78	86	120
H	85	115	115	157.5	157.5	85	115	115	157.5	157.5
M/ISO clamp	21	21	21	21	21					
M/DIN clamp						21	21	28	28	28
M/DIN male						22	23	25	25	30
M/SMS male	20	20	24	24	35					
Weight (kg)	7.3	9.5	10.5	16.4	18.6	7.3	9.5	10.5	16.4	18.6

**Air Connections Compressed air:**


R 1/8" (BSP) internal thread for actuator.

Electrical connections

**Positioner 8694**  
without display



**Positioner 8692**  
with display



Alfa Laval reserves the right to change specifications without prior notification.

**How to contact Alfa Laval**

Contact details for all countries  
are continually updated on our website.  
Please visit [www.alfalaval.com](http://www.alfalaval.com) to  
access the information direct.

[www.sks-online.com](http://www.sks-online.com)

